



Pigment Concentrate 668

For tinting or shading wooden or mural surfaces.

Application range:

Even a small addition of the LEINOS 668 pigment concentrate has a very high colouring power. Pigment concentrate 668 cannot be used alone as the only colouring agent. Pearl lustre pigments can only be used for LEINOS 646 Glaze Binder.

Colour:

In order to give your designs as much space as they need, we have developed a selection of 22 colours as well as 2 pearlescent pigments:

303 Iron oxide red,
306 Iron oxide mahogany,
307 Oxide yellow,
309 Ochre yellow,
311 Ochre havanna,
312 Ochre red,
313 Ochre rustbrown,
320 Ebony black,
323 Ultramarine blue *,
324 Ultramarine violet *,
326 Sun yellow,
327 Orange,
328 Spinel blue,
329 Spinel green,
330 Spinel turquoise,
331 White,
332 Pompeian red,
333 Corn yellow,
335 Ultramarine red *,
336 Ultramarine red violet *,
337 Turkey dark red *,
338 Turkey light red *,

Pearlescent pigment colours:

340 Sterling silver * **,
345 Gold satin * **

* not suitable for lime paint

** not miscible with each other

Full declaration:

Water, shellac soap, natural resin soap, bees wax, carnauba wax, methyl cellulose, mineral pigments, benzisothiazolinone, zinc pyrithion. The VOC content of this product is < 1 g/l. EU limit value max 30 g/l (class "a" 2010).

Container sizes and coverage:

Je nach Einsatzzweck und gewünschter Farbintensität unterschiedlich.

Sizes

0,1l

0,5l

Storage:

Keep in a sealed container in a cool place. Protect from frost!

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 20.

Cleaning:

With water and LEINOS 930 soap of vegetable origin.

Hazard statements:

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Hotline for allergy sufferers: ++49 (0) 04163 - 86 747 0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: May 13, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de