



Anti-Greying Fluid 940

New colour for all greying timber without sanding...

Apply Anti-Greying Fluid, let react and then brush thoroughly, for example with a scrubbing brush and plenty of water. You'll be surprised how quickly you achieve excellent results ...

Application range:

For all types of hard and soft wood. Can be applied to garden furniture as well as grey patio wood, terraces etc.

Technical qualities:

Excellent cleaning and anti- ageing effect through brightening the wood. Effective on hard and soft woods with the active ingredients of coconut fatty acid and oxalic acid.

Full declaration:

Water, oxalic acid, coconut tenside, methyl cellulose, vegetable-based emulsifier.

Application:

Stir well before use. Apply a thin coat by cloth or brush. Do not apply in direct sun light as it may speed up drying time. If applied at high temperatures, lightly spray surface with water and leave to soak in for at least 15 minutes or up to 1 hour in case of severe greying. Clean with brush or abrasive web and water. Rinse thoroughly with water to neutralize and to remove dirt. Let dry for 1 - 2 days. After this treatment the surface may be a little rough and depleted. Slightly sand surface and protect with LEINOS Teak Oil 223 or Terrace Wood Oil 236.

Container sizes and coverage:

100 - 125 ml/m² on smooth surfaces. Rough sawn or profiled wood surfaces can cause additional consumption.

Sizes	Coverage...*
0,5l	4,5 m ²
2,5l	23 m ²

* Coverage per coat

Storage:

Under cool and dry conditions. Keep tightly sealed. Shelf life at least 2 years if unopened.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 07 06 01

Cleaning:

Clean immediately with water after use.

Hazard statements:

Safety data sheet available on request.



To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: January 21, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de