



# Oil Refurbisher Clear 285

For maintaining and preserving. Also suitable for use by allergy sufferers, subject to medical consultation!

**Application range:**

For maintaining all interior oiled and waxed surfaces such as wooden floors, cork flooring and derived timber products. Suitable for linoleum.

**Technical qualities:**

Transparent, easy to apply, satin finish, moisture repellent, antistatic effects. DIN EN 71 Part 3 certified as suitable for toys. Resistant to perspiration and saliva according to DIN 53160.

**Colour:**

002 Clear

**Full declaration:**

Linseed oil, wood oil, linseed stand oil, castor oil, natural resin ester, isoparaffinic hydrocarbons, zinc oxide, alumina, kaolin, micro wax, silicic acid, drying agents. The VOC content of this product is 660 g/l. EU limit value max 700 g/l (class "f" 2010).

**Application:**

The surface must be dry, solid, clean and free of dust and grease. Clean surface with Leinos Vegetable Soap 930 and rinse with water. Let the surface dry. The product is ready for use. Apply thinly and evenly at temperatures above 15°C. After 20 minutes work with a polishing felt pad. Remove the excess of oil carefully and polish with a white felt pad. Apply a second coat on poor and exhausted surfaces or on surfaces exposed to wear and tear. Surfaces exposed to wear and tear can also be treated with Leinos Hardwax Oil 290. Lower temperatures will delay the drying process. Always apply a test coat. Ensure good light and ventilation conditions during use and drying times.

**Drying time:**

At 20°C and 50 - 55% relative humidity: first coat 6 - 12 hours, ready for sanding and coating. Floors can be used with care after one day. Final degree of hardening is reached after 7 - 10 days.

**Container sizes and coverage:**

Approx. 30 - 40 ml/m<sup>2</sup> (25 - 35 m<sup>2</sup>/l), depending upon the condition and absorbency of the surface.

**Sizes Coverage...\***

0,25l

0,75l **Je nach Beanspruchung und Einsatz**

2,5l

10l

\* Coverage per coat

**Storage:**

Under cool and dry conditions. Close lid tightly when not in use. Once package has been opened film forming can appear. Skim off film before use. Shelf-life of unopened container 5 years.

**Disposal:**

According to locally regulated laws European Waste Catalogue (EWC) 08 01 11.

**Cleaning:**

Clean equipments immediately after use with Thinner 200.

**Hazard statements:**

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.

Safety data sheet available on request.

Achtung! Beim Sprühen können gefährliche lungengängige Tröpfchen entstehen. Aerosol oder Nebel nicht einatmen.

GHS08



Danger

**Precautionary statements:**

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials.

During sanding wear mask against respirable dust.

---

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: July 12, 2025

---

**LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany**

**Tel. +49 (0) 41 63 - 86 74 7-0 • [www.LEINOS.de](http://www.LEINOS.de) • [info@LEINOS.de](mailto:info@LEINOS.de)**