

# Wooden Floor Soap Clear 924

## For cleaning and maintaining surfaces treated by soaping or leaching.

### Application range:

For cleaning, maintai- ning and refining surfaces treated by soaping or leaching, for wooden surfaces treated with natural coloured or white oil. For the initial treatment of softwood floorings exposed to normal wear and tear in living rooms, bedrooms, for panelling, furniture and doors. Also for intensive cleaning of heavily soiled exterior surfaces like decks, fences, doors, flagstones or brickwork. Ideally suited for cleaning and removing infestations of mould and algae. Highly concentrated.

### **Technical qualities:**

Liquid, high yield, strong cleaning efficiency, lipid regulating. Made of pure vegetable and renewable materials.

**Colour:** 

002 Clear, 202 White.

### Full declaration:

Water, coconut oil surfactants, potassium soaps made of soy oil and palm oil, polyaspartic acid, (white: titanium dioxide). The surfactants are biodegradable according to the Detergent Regulation (EC) No. 648/2004.

### **Application:**

Apply at temperatures above 8 °C. Intensive cleaning: Dilute the concentrate with warm water in a ratio of 1:20 up to 1:40 depending on the degree of soiling (e.g mixture of 250 ml Wooden Floor Soap and 5 - 10 litres of water). Apply evenly by a bigger brush. The treated surface must be sufficiently wet. Let react for 20 minutes and scrub/wash the surface thoroughly. Repeat cleaning if necessary. Rinse the surface with water and let dry. If desired apply Natural Timber Oil 236 for protection outdoors. Hint: In case of heavy fungal and algae decay let react the Wooden Floor Soap for 3 - 4 days. Afterwards rinse thoroughly with water and treat remaining spots with a hard brush.

### Container sizes and coverage:

Intensive cleaning: 1 L diluted concentrate (1:20 - 1:40) covers approx. 120 - 150 m<sup>2</sup>. Initial treatment: 1 L diluted

concentrate (1:10) covers approx. 10 - 25 m<sup>2</sup>. Maintaining: 1 L diluted concentrate (1:40) covers approx. 400 - 600 m<sup>2</sup>.

Sizes Coverage ...\*

### 1I Je nach Verschmutzung

### 2.51

\* Coverage per coat

### Storage:

Store dry, cool and sealed. Originally sealed at least 2 years stable.

### Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 07 06 01.

### Cleaning:

Immediately with water.

### Hazard statements:

Causes skin irritation. Causes serious eye irritation. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

GHS07



### **Precautionary statements:**

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Keep out of reach of children.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: September 16, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de