



Impregnation Primer 150

Protects the coating against blue-staining fungi.

Application range:

Open-pored impregnating for all absorbent surfaces of wood outdoors, protects the coat against blue-staining fungi. The Impregnation Primer penetrates deeply and guarantees a solid basis for further coatings.

Technical qualities:

Transparent, slightly milky. Light coloured absorbent surfaces may get a bit darker after drying.

Full declaration:

Linseed oil, wood oil, linseed stand oil, isoparaffinic hydrocarbons, jodo-propynyl-butyl-carbamate, drying agents. The VOC content of this product is 360 g/l. EU limit value max 700 g/l (class "f" 2010).

Application:

Stir well before use. Apply undiluted and evenly by brush, rolling, spraying or dipping. Apply first coat abundantly, wait 20 minutes, then spread any excess of unabsorbed oil carefully onto spots that are still absorbent. The surface must be thoroughly dry and saturated before further treatment is possible.

Drying time:

At 20°C and 50 - 55% relative humidity: first coat drying time is 16 - 24 h. Ensure good light and ventilation conditions during use and drying times. Otherwise a lingering odour of plant oils possible.

Container sizes and coverage:

Approx. 60 - 80 ml/m² per coat depending upon the condition and absorbency of the surface. Always do a test coat.

Sizes	Coverage...*
0,75l	11 m ²
2,5l	36 m ²
10l	144 m ²
30l	432 m ²

* Coverage per coat

Storage:

Under cool and dry conditions. Shelf life 2 years. Close lid tightly when not in use.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 11.

Cleaning:

Clean equipments immediately after use with LEINOS Thinner 200.

Hazard statements:

May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction. Active ingredient: Iodo-2-propynyl-butylcarbamate <0,6% Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.



IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials.

During sanding wear mask against respirable dust.

Hotline for allergy sufferers: ++49 (0) 04163 - 86 747 0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: February 1, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de