



Primer Oil 220

Suitable for open-pored priming of all interior and exterior absorbent surfaces. Without protection against mould.

Technical qualities:

High penetrating power, remains elastic. Supplies the deep contact with wood necessary for all subsequent coatings. Water vapour permeable.

Colour:

Transparent. Colourless to slightly yellow. Woodwork will react differently in colour according to the nature of the wood and the structure of the wood grain.

Full declaration:

Linseed oil, isoparaffins, drying agents. The VOC content of this product is 400 g/l. EU limit value max 700 g/l (class "f" 2010).

Application:

Stir well before use. Apply undiluted by brush, roller, spray or dipping technique.

Drying time:

Approx. 16 - 24 hours. It is essential to provide adequate ventilation during the drying process!

Container sizes and coverage:

Approx. 60 - 80 ml/m² per coat, may vary according to the absorbency of the surface.

<i>Sizes</i>	<i>Coverage...*</i>
0,75l	11 m ²
2,5l	36 m ²
10l	144 m ²
30l	432 m ²

* Coverage per coat

Storage:

Originally sealed at least 5 years stable. Store dry, cool and sealed.

Disposal:

According to locally regulated laws European Waste Catalogue (EWC) 08 01 02.

Cleaning:

LEINOS Thinner 200. Product is ready for application.

Hazard statements:

May be fatal if swallowed and enters airways.

Repeated exposure may cause skin dryness or cracking.

Safety data sheet available on request.

GHS08



Danger

Precautionary statements:

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials.

During sanding wear mask against respirable dust.

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: February 1, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de