



Quick Sanding Primer 625

Short drying time, water based.

Application range:

Fast and hard-wearing pre- treatment for all absorbent solid wood, for interior areas.

Technical qualities:

Water-based primer, fast drying and easy to sand, gives an even colouring and prevents the oils to sink into the wood too deeply. Recommended application after a short drying time: LEINOS Oils like LEINOS Hard Oil 240 or LEINOS Hard Oil special 245.

Colour:

Yellowish.

Full declaration:

Water, shellac, ethanol, potash, methyl/benzisothiazolinone.

Application:

By brush or roller. After a short drying time of approx. 45 minutes sand the surface with 240 grain. Ambient and surface temperature must be higher than +15°C.

Thinning:

Use water for dilution. Clean equipments immediately after use with water and LEINOS Vegetable Soap 930.

Drying time:

At 20°C and 50% relative humidity: drying time approx. 45 minutes, depending on type of wood and amount applied.

Container sizes and coverage:

Approx. 90 ml/m² depending on the absorbency of the wood.

Storage:

Under cool and dry conditions, prevent from freezing. Shelf life of unopened containers 2 years.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 20

Hazard statements:

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Hotline for allergy sufferers: +49 (0) 04163 - 86 747 0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: December 21, 2024
