



Teak Oil 223

For the first-time treatment and care of exterior woodwork.

Application range:

Teak Oil is a high quality product based on vegetable oils and resins for all types of exterior wood such as fences, pergola, play ground timber, wooden terraces and decks, teak furniture and garden furniture. Suitable especially for tropical woods such as bangkirai and teak.

Technical qualities:

Quick and easy to apply. High-quality vegetable oils impregnate new woods and refreshes old ones. The vegetable oils maintain the wood sound and elastic and prevent desiccation. Best refreshing for oiled timber. No sanding required for further coatings. Good refreshing of old coatings. Saliva- and perspiration resistant according to DIN 53160.

Colour:

Transparent, colourless to slightly yellow. Light and absorbent surfaces will dry slightly darker. Woodwork will react differently in colour according to the nature of the wood and the structure of the wood grain.

Full declaration:

Linseed oil, castor oil, wood oil, isoparaffins, iodo-propynyl-butylcarbamate, drying agents. Product contains max 420 g/l VOC. EU limit value for this product (cat. f): 700 g/l (2010).

Application:

Stir well before use. Apply by brush thinly and evenly. Avoid ponding. Ambient- and surface temperature must be higher than +10°C.

Drying time:

Approx. 16 - 24 hours. It is essential to provide adequate ventilation during the drying process!

Container sizes and coverage:

Approx. 50 - 70 ml/m² per coat depending on the absorbency of the surface.

Sizes	Coverage...*
0,25l	4 m ²
0,75l	12,5 m ²
2,5l	41,5 m ²

* Coverage per coat

Storage:

Originally sealed at least 2 years stable. Store dry, cool and sealed.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 11.

Cleaning:

LEINOS Thinner 200. Product is ready for application.

Hazard statements:

Harmful to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.



Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction.

Active ingredient: Iodo-2-propynyl-butylcarbamate <0,6%

Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials.

During sanding wear mask against respirable dust.

Hotline for allergy sufferers: ++49 (0) 04163 - 86 747 0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: July 31, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de