



Terrace Wood Oil 236

Especially suitable for untreated and oiled wood in need of deep impregnation.

Natural Timber Oil refreshes old wood, maintains the wood sound and elastic, protects against the weather and provides a good UV-protection (except colourless). Enjoy the simple and quick application.

Application range:

For all types of exterior wood such as fences, pergola, play ground timber, wooden terraces and decks, teak furniture and garden furniture. Suitable especially for tropical woods such as bangkirai and teak.

Technical qualities:

Quick and easy to apply. High-quality vegetable oils impregnate new woods and refresh old ones. The vegetable oils maintain the wood sound and elastic and prevent desiccation. High water resistance. No sanding required for further coatings. Good refreshing of old coatings.

Colour:

002 Colourless, 015 Brownish, 052 Reddish

Full declaration:

Linseed oil, wood oil, castor oil, isoparaffins, alumina, mineral pigments, jodopropynyl-butylcarbamate, drying agents. Natural Wood Oil contains max 450 g/l VOC. EU limit value for this product (cat. f): 700 g/l (2010).

Application:

Stir well before use. The product is ready for use. The surface must be dry, clean and free of dust and grease. Apply thinly and evenly at temperatures above 10°C. Lower temperatures will delay the drying process. Avoid ponding. Always apply a test coat. Ensure good light and ventilation conditions during use and drying times.

Drying time:

At 20°C and 50 - 55% relative humidity first coat drying time is 6 - 8 hours. Allow rough wood to dry thoroughly during 1 - 2 days.

Container sizes and coverage:

Approx. 40 - 70 ml/m², depending upon the condition and absorbency of the surface.

Sizes	Coverage...*
0,25l	4 m ²
0,75l	12,5 m ²
2,5l	41,5 m ²
10l	166 m ²

* Coverage per coat



Storage:

Under cool and dry conditions. Close lid tightly when not in use. Once package has been opened film forming can appear. Skim off film before use. Shelf-life of unopened container 2 years.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 11.

Cleaning:

Clean equipments immediately after use with LEINOS Thinner No. 200.

Special advice:

Colour specifications and colour prints are non-binding. Colour deviations are possible depending on batch, surface and printing technique. The dried original colour shade differs from the fresh colour shade in the container. Therefore, a test coat with colour matching is essential. Mix different different batches of the same colour shade.

Hazard statements:

Harmful to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.

Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction.

Active ingredient: Iodo-2-propynyl-butylcarbamate <0,5%

Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials.

During sanding wear mask against respirable dust.

Hotline for allergy sufferers: ++49 (0) 04163 - 86 747 0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: April 2, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de