



# Countertop Oil SF 283

Water and dirt resistant, resistant to abrasion, for all wooden countertops indoors.

**Application range:**

For the impregnation of kitchen countertops, furniture surfaces and wooden toys.

**Technical qualities:**

Oil-wax-mixture. Solvent free, hard-wearing, impregnating, water repellent, open-pored. Accentuates the natural wood grain. DIN EN 71 Part 3 certified as suitable for toys. German Industrial Norm (DIN) 53160 certified for colour fastness when exposed to perspiration and saliva. Water resistant according to DIN 68861 Part 1.

**Full declaration:**

Linseed oil, wood oil-stand oil, nut oil, micro wax, alumina, kaolin, zinc oxide, aluminium silicate, drying agents. The product contains max 1 g/l VOC. EU limit value for this product (cat. e): 400 g/l (2010)

**Application:**

The surface must be dry (humidity of the wood max 14%), clean and free of dust and grease. The surface must be sanded up to 240 grain. Apply at temperatures above 16°C. Lower temperatures will delay the drying process. Stir well before use. Apply by brush, sponge, lint free cloth or with a roller.

**Drying time:**

The drying time is strongly depending on the ambience. At 20 - 23 °C the drying time is 6 -12 hours depending on the amount of oil applied. Ensure good light and ventilation conditions during use and drying times. Otherwise a lingering odour of plant oils possible.

**Container sizes and coverage:**

Always do a test coat. Average applied quantity: 20 - 30 g/m<sup>2</sup> depending upon the condition and absorbency of the surface.

Sizes	Coverage...*
0,75l	18 m <sup>2</sup>
2,5l	60 m <sup>2</sup>
10l	240 m <sup>2</sup>

\* Coverage per coat

**Storage:**

Under cool and dry conditions. Shelf life of unopened container 5 years. Close lid tightly when not in use.

**Disposal:**

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 12

**Cleaning:**

Clean equipments immediately after use with Thinner No. 750.

**Hazard statements:**

Harmful to aquatic life with long lasting effects.  
Safety data sheet available on request.

**Precautionary statements:**

Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container according to local regulations. Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion. A typical smell may arise due to the natural raw materials. During sanding wear mask against respirable dust.

---

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: December 30, 2024

---

**LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany**  
**Tel. +49 (0) 41 63 - 86 74 7-0 • [www.LEINOS.de](http://www.LEINOS.de) • [info@LEINOS.de](mailto:info@LEINOS.de)**