



# Parquet Oil LF 253

For wooden floorings, Sterling OSB-boards and similar surfaces.

**Application range:**

For wooden floorings, Sterling OSB-boards and similar surfaces.

**Technical qualities:**

Parquet oil LF is made of oils and waxes, solvent free, refines the wood permanently and guarantees a hard-wearing surface. Accentuates the natural wood grain, satin finish. German Industrial Norm (DIN) 53160 certified for colour fastness when exposed to perspiration and saliva after two coatings.

**Full declaration:**

Linseed oil, castor oil-natural resin-ester, wood oil-stand oil, wood oil-castor oil-stand oil, micro wax, alumina, kaolin, drying agents. The product contains max 1 g/l VOC. EU limit value for this product (cat. e): 400 g/l (2010).

**Application:**

The surface must be dry (humidity of the wood max 14%), clean and free of dust and grease. Apply at temperatures above 16 °C. Lower temperatures will delay the drying process. The product is ready for use. Apply one coat evenly by a double-face spatula (approx. 15 - 30 ml/m<sup>2</sup>, depending on the absorbency of the wood). First polish thoroughly with a green felt pad and polish afterwards the surface with a white pad. For surfaces exposed to wear and tear or highly absorbent surfaces apply a second coat sparingly after 24 hours. Polish the surface with a white pad after 20 - 30 minutes. Please note: the floorings must be laid jointless or levelled out with a filler. Joints may cause oil leakage or noise development during use. Always apply a test coat. Ensure good light and ventilation conditions during use and drying times.

**Drying time:**

At 20°C and 50 - 55% relative humidity: approx. 6 - 12 hours. Fully hardened after 7 - 10 days.

**Container sizes and coverage:**

15 - 30 ml/m<sup>2</sup>; Yield: 40 - 50 m<sup>2</sup>/litre.

Sizes	Coverage...*
0,75l	34 m <sup>2</sup>
2,5l	113 m <sup>2</sup>
10l	450 m <sup>2</sup>

\* Coverage per coat

**Storage:**

Under cool and dry conditions. Close lid tightly when not in use. Shelf-life of unopened container 5 years.

**Disposal:**

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 12.

**Cleaning:**

LEINOS Thinner 200. Clean equipments immediately after use.

**Hazard statements:**

Harmful to aquatic life with long lasting effects. Safety data sheet available on request.



**Precautionary statements:**

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product.

The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials.

During sanding wear mask against respirable dust.

---

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: September 13, 2025

---

**LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany**

**Tel. +49 (0) 41 63 - 86 74 7-0 • [www.LEINOS.de](http://www.LEINOS.de) • [info@LEINOS.de](mailto:info@LEINOS.de)**