



Rapid Oil LF 249

Solvent-free, quick one-off treatment or repair of wood surfaces that are not subject to heavy wear. Pasty oil-wax combination, therefore very good polishing properties.

Application range:

One-coat impregnation of all interior wooden surfaces. Not suitable for kitchen countertops, staircases and floors.

Technical qualities:

Solvent free, impregnating, film-forming, elastic, antistatic. Complies with German Industrial Norm DIN 53160 fastness to perspiration and saliva.

Colour:

Transparent, clear.

Full declaration:

Safflower oil, sunflower oil, linseed oil, wood oil, ricin oil, natural resin ester, beeswax, carnauba wax, micro wax, drying agents. The product contains max 1 g/l VOC. EU limit value for this product (cat.f): 700 g/l (2010)

Application:

The surface must be dry, clean and free of dust and grease. Stir well before use. Cold or hot application by brush at room temperatures above 15°C. Let impregnate for 1 - 24 hours and polish with a pad. No drying possible in the meantime because the product does not contain any surface dryers.

Drying time:

At 20°C and 50 - 55% relative humidity: 24 hours. Exposure to warm air will reduce the drying time considerably.

Container sizes and coverage:

First coat: 10 - 15 ml/m², depending upon the condition and absorbency of the surface. Always do a test coat. Stir well before use. Ensure good light and ventilation conditions during use and drying times.

<i>Sizes</i>	<i>Coverage...*</i>
0,25l	18 m ²
0,75l	50 m ²
2,5l	160 m ²

Storage:

Under cool and dry conditions. Close lid tightly when not in use. Once package has been opened film forming can appear. Skim off film before use. Shelf-life of unopened container 2 years.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 11.

Cleaning:

LEINOS Thinner 200. Clean equipments immediately after use.

Hazard statements:

Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container according to local regulations. Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the

product. The product alone will not undergo spontaneous combustion. A typical smell may arise due to the natural raw materials. During sanding wear mask against respirable dust.

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: November 21, 2024

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de