

Mould Exx 960

For removing safely mildew indoors.

Without chlorinated substances.

Application range:

For disinfection of mould decay, without chlorinated substances.

Technical qualities:

Liquid.

Colour:

Colourless.

Full declaration:

Ethanol (70g/) - denatured, water and cedar wood oil.

Application:

Spray product generously on infected patches, let dry and remove by brushing and suction cleaning. If necessary repeat procedure. Good ventilation recommended! In case of heavy decay the plaster should be removed and the wall be treated with lime plaster.

Container sizes and coverage:

100 - 150 ml/m².

Sizes	Coverage...*
0,5l	4 m ²
1l	8 m ²

* Coverage per coat



Storage:

Cool and dry.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 07 07 04

Cleaning:

With water.

Hazard statements:

Highly flammable liquid and vapour. Contains cedar wood oil. May cause allergic reactions. Safety data sheet available on request.

GHS02



Danger

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking. Keep container tightly closed.

Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Store in a well-ventilated place. Keep cool.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Hotline for allergy sufferers: ++49 (0) 04163 - 86 747 0

UN-No. 1170

Use LEINOS Mould Exx carefully. Always read the label and product information before use. The use of biocidal products should be kept to a minimum.

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: February 14, 2026

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de