



Wood Varnish Mix 263

Weatherproof and water resistant open-pored protective coating for all interior wooden surfaces.

Application range:

Weather- and water-resistant protection for wood indoors: for doors, fences and other interior wooden surfaces. Without film protection against fungal attack, only for interior use.

Technical qualities:

Transparent and water repellent, water vapour permeable. Tested according to the criteria of the ihd and ift Rosenheim for discoloration by mortar, vapour permeability, compatibility with sealing profiles and weathering stability. Migration behaviour tested according to DIN EN 71, part 3. Saliva- and perspiration resistant according to DIN 53160. Not suitable for permanently exposed woods to water.

Full declaration:

Wood oil, ricin oil, linseed oil, natural resin ester, isoparaffins, micro wax, zinc oxide, mineral pigments, drying agents. The VOC content of this product is max 480 g/l. EU limit value max 700 g/l (class "f" 2010).

Application:

Stir well before use. The product is ready for use. The surface must be dry, clean and free of dust and grease. Apply thinly and evenly at temperatures above 15°C. Lower temperatures will delay the drying process. Always do a test coat.

Drying time:

At 20°C and 50 - 55 % relative humidity: first coat drying time is 16 - 24 hours. This system requires sufficient oxygen in the air for drying. Therefore, ensure good ventilation, with a fan in stagnant air, also to avoid the buildup of odors.

Container sizes and coverage:

Approx. 60 - 80 ml/m², depending upon the condition and absorbency of the surface. Apply sparingly to avoid delay of drying process.

<i>Sizes</i>	<i>Coverage...*</i>
0,75l	11 m ²
2,4l	36 m ²

* Coverage per coat

Storage:

Under cool and dry conditions. Shelf-life of unopened container 2 years.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 11.

Cleaning:

Clean equipments immediately after use with LEINOS Thinner No. 200.

Special advice:

Colour specifications and colour prints are non-binding. Colour deviations are possible depending on batch, surface and printing technique. The dried original colour shade differs from the fresh colour shade in the container. Therefore, a test coat with colour matching is essential. Mix different different batches of the same colour shade.

Hazard statements:

Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container according to local regulations. Always be sure to store

cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product. The product alone will not undergo spontaneous combustion. A typical smell may arise due to the natural raw materials. During sanding wear mask against respirable dust.

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: September 13, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de