



# Furniture Chalk Paint 637

## Covering chalk paint for renovation indoors

**Application range:**

Open pored chalk paint according to DIN EN 13300 with very good covering power, easy to apply and versatile. For easily stressed surfaces indoors, e. g. furniture, wall paneling etc.

**Technical qualities:**

Solvent-free, good filling and covering capacities, easy to process, high yielding. Wash resistant to DIN / EN ISO 11998 and DIN EN 13300, class 3. Wet abrasion class 3. Tested according to EN 71-3.

**Colour:**

630 Mint, 631 Ice Blue, 632 Savannah, 634 Vanilla, 635 Cream, 636 Tuscany Red, 637 Pacific Blue, 638 Stone Grey, 639 Dark Grey, 640 White

**Full declaration:**

Water, chalk, titanium dioxide, pigments, talc, calcite, natural resins, polymeric starch ester, methylcellulose, isothiazolinones. The VOC content of this product is max. 1 g/l. The EU limit value is max. 30 g/l (category „a“ from 2010).

**Application:**

Stir carefully before use! The substrate must be dry and free of dust and grease. Old coats of paint must be sanded down and completely removed if they are flaking. To make the surface even more hard-wearing, we recommend treating it with the Wall Wax Finish. It can be applied by brush or roller. At room temperatures above 8 °C.

**Drying time:**

At 20 °C and 50 % relative humidity, surface drying after approx. 1-2 h. Thoroughly dried after approx. 12 h. Ensure good light and ventilation conditions during use and drying times. This system requires sufficient amounts of oxygen, a dry surface and a relative humidity that is not too high. Therefore, only work on a dry surface and provide good aeration, eg with a fan. Otherwise a lingering odour of plant oils possible.

**Container sizes and coverage:**

Approx. 80 - 120 ml/m<sup>2</sup> per coat, may differ depending on the absorbency of the surface. Always do a test coat.

**Storage:**

Under cool and dry conditions, prevent from freezing. Shelf life of unopened containers 12 months.

**Disposal:**

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 20.

**Cleaning:**

Clean equipments immediately after use with water.

**Hazard statements:**

Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Safety data sheet available on request.

**Precautionary statements:**

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Dispose of contents/container according to local regulations. Hotline for allergy sufferers: +49 (0) 4163 - 86 74 70

---

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

**LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany**  
**Tel. +49 (0) 41 63 - 86 74 7-0 • [www.LEINOS.de](http://www.LEINOS.de) • [info@LEINOS.de](mailto:info@LEINOS.de)**