

# Vintage Wall Ground 631

Short drying time, water based. Water-based, low-solvent, non-yellowing.

## **Application range:**

For the exclusive and breathable wall decoration of the living area.

## **Technical qualities:**

Once thorougly dry nearly colourless and transparent Vintage Wall Ground. Water vapour permeable. Capable of being pigmented with LEINOS Pigment Concentrate 668. LEINOS Pearlescent Effect Pigments 668 are not suitable for the colouring of the Vintage Wall Ground.

#### Colour:

Without pigmentation nearly colourless once thoroughly dry.

#### **Full declaration:**

Water, shellac, carnaubawax, bees wax, methyl cellulose, natural resin soap, talcum, calcium carbonate, alumina and benzisothiazolinone. Product contains max 1 g/l VOC. EU limit value for this product (cat. a): 30 g/l (2010).

## Application:

With a Japanese trowel or other suitable similar trowels. Ambient- and surface temperature must be higher than +15°C.

#### Drying time:

Ready to be smoothed over after 2 - 3 hours, ready for polishing after approx. 24 hours.

## Container sizes and coverage:

Approx. 30 - 70 g/m<sup>2</sup> per operation according to the application method and the desired design.

Sizes	Coverage*
0,751	11 - 23 m <sup>2</sup>

<sup>\*</sup> Coverage per coat

#### Storage:

Originally sealed at least 12 months stable. Store dry, cool and sealed. Protect from frost!

#### Disposal:

In accordance with local, official regulations. Dried product residues can be disposed of with household waste. Waste code EWC 08 01 12.

#### Cleaning:

Water and LEINOS Vegetable Soap 930. Product is adjusted ready for application.

## **Hazard statements:**

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Safety data sheet available on request.

## **Precautionary statements:**

Keep out of reach of children.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Hotline for allergy sufferers: +49 (0) 04163 - 86 747 0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product

properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: August 31, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de