

Clay Mix 656

For interior use, regulates humidity, solvent free, breathable.

Application range:

For all interior absorbent mineral surfaces, especially clay walls. Also suitable for OSB-boards. Base paint for automatic LEINOS tinting machines.

Technical qualities:

Solvent free, permeable to water vapour. The dull surface regulates humidity within the home.

Full declaration:

Water, clay, chalk, cellulose, titanium dioxide, vegetable emulsifier, polyaspartic acid, starch-ester polymer, isothiazolinone. Product contains max 1 g/l VOC. EU limit value for this product (cat. a): 30 g/l (2010).

Preparation:

The surface must be dry, clean, absorbent and free of dust and grease. Test coat recommended. Stir well before use and during application. Apply by roller or brush, smooth out in all directions. One coat will suffice as a rule. Always apply a test coat. Ensure good light and ventilation conditions during use and drying times.

Drying time:

At 20°C and 50% relative humidity: Drying time is 6 - 12 h.

Container sizes and coverage:

1 l covers approx. 6,5 m².

Sizes	Coverage...*
2,5l	15 m ²
5l	30 m ²
10l	60 m ²

* Coverage per coat

Storage:

Under cool and dry conditions, prevent from freezing. Shelf life of unopened containers 12 months. After opening use product within 2 days.

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 20.

Cleaning:

Clean equipments immediately after use with water and Leinos Vegetable Soap No. 930.

Hazard statements:

Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children. Do NOT induce vomiting. Dispose of contents/container according to local regulations. Hotline for allergy sufferers: +49 (0) 4163 - 86 74 70

Sheet, all previous information becomes invalid.

Status: February 8, 2026

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de