



Deep sealer 620

Primer for absorbent bases before treatment with LEINOS wall paints and plaster.

Application range:

For priming absorbent substrates before further treatment with LEINOS wall paints, such as Casein Wall Paint 640, Natural Resin Emulsion Paint 660 or Plaster Effect Paint 680.

Technical qualities:

Transparent deep sealer. Highly vapour permeable.

Full declaration:

Water, soaps of shellac and natural resins, carnauba wax, bees wax, cellulose, potassium carbonate, benzisothiazolinone. The VOC content of this product is max 1 g/l. EU limit value max 30 g/l (class "a" 2010).

Preparation:

To achieve optimum results, please refer to the technical data sheets for all products used. Suitable substrates are all types of plaster, porous stone, plasterboard and old coats of wall paint. The substrate must be dry, clean and free of dust and grease, but may have a slightly acidic or alkaline chemical reaction.

Application:

Brush, roller. Temperature of the surroundings and the surface over 15°C. The product must be thinned 1:1 with water before application.

Drying time:

2 - 4 hours.

Container sizes and coverage:

Approx. 60 -100 ml/m² of the thinned product, depending on the absorbency of the substrate.

Sizes	Coverage...*
1l	25 m ²
2,5l	62 m ²
10l	250 m ²

* Coverage per coat

Storage:

Stable for about 12 months if unopened. Keep in a sealed container in a cool place. Protect from frost.

Disposal:

European Waste Catalogue (EWC) 08 01 20

Cleaning:

Water and LEINOS 930 soap of vegetable origin.

Hazard statements:

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Hotline for allergy sufferers: ++49 (0) 04163 - 86 747

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: February 5, 2026

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de