



Interior Smoothing and Texturing Filler 684

The ideal wall filler for all interior work. Easy to apply. Dries without cracks, even in large layer thickness. Can be coloured as required with LEINOS pigment concentrates.

Application range:

For interior use for finishing walls and ceilings. For filling cracks and holes as well as joints between plasterboard and other building boards. For securing wall plugs and inserting fixtures during installation work. For decorating walls and ceilings with texturing filler.

Colour:

White, matt. Ready mixed and can be coloured as required using LEINOS pigment concentrate 668. See technical data sheet 668.

Full declaration:

Finely ground calcium sulphate (natural gypsum), calcium carbonate and methyl cellulose.

Preparation:

The base to be treated must be clean, firm, dry and good bearing. Dust, dirt, wallpaper, paint which is not securely adhering or only weakly bonded as well as flaking or loose plaster must be removed. Mixing ratio: 2 parts by volume of smoothing and texturing filler to 1 part by volume of water. Stir briefly after 2 - 3 minutes.

Application:

For filling holes and cracks press the 684 smoothing and texturing filler down into the recess and smooth off. For making good smooth surfaces rub down as required and dampen evenly with a sponge board and smooth off. The layer of filler must be completely dry for all subsequent work, such as, for example, rubbing down, over-papering, painting. For fixing plasterboard slabs or walling slabs apply the 684 smoothing and texturing filler in small lumps to the back of the slabs, press them into position and align them.

Container sizes and coverage:**Sizes Coverage...*****1kg****5kg** Depending on application thickness

* Coverage per coat

Storage:

Protect against damp. Store well-sealed in a dry place.

Cleaning:

Water and LEINOS 930 vegetable soap.

Special advice:

When filling in the joints between plasterboard slabs it is possible to dispense with the insertion of reinforcing strips, if the slabs are of an appropriate design.

Hazard statements:

Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children. Avoid release to the environment. Dispose of contents/container according to local regulations.

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: September 16, 2024

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany

Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de