



Wall Wax Finish 350

Water-based, low-solvent, non-yellowing.

Application range:

Finish for post-treatment of surfaces that have been designed with Natural Resin Dispersion Paint 660, Glaze Filler 630 or Wall Wipe Glaze 601.

Technical qualities:

Open-pored protective film made from natural raw materials. Protects designed surfaces against dirt and mechanical abrasion. Increases wipe resistance.

Full declaration:

Nut oil, safflower oil, natural resin ester, micro wax, alumina, isoparaffins, benzisothiazolinone, drying agents. The VOC content of this product is max. 430 g/l. The EU limit value is max. 700 g/l (category F from 2010).

Application:

Apply sparingly with a terry cloth, roller or brush. Room and surface temperature above 15°C.

Thinning:

LEINOS Thinner 200.

Container sizes and coverage:

Approx. 35 ml/m² per application. Use sparingly to avoid drying problems.

<i>Sizes</i>	<i>Coverage...*</i>
0.75l	21,5 m ²
2.5l	71,5 m ²

* Coverage per coat

Storage:

Store in a cool but frost-free place. Close container tightly after use.

Disposal:

In accordance with local, official regulations. Dried product residues can be disposed of with household waste. Waste code EAK 08 01 11.

Hazard statements:

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Hotline for allergy sufferers: +49 (0) 41 63 - 86 74 7-0

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: February 5, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de