



White Emulsion Paint 650

Low odour, VOC-free, breathable.

Application range:

For white or coloured opaque coatings with good water vapor permeability on mineral bases or on wallpaper with firm and good adhesion.

Technical qualities:

Good hiding power, easy to apply, high yield. VOC-free, non-yellowing, water vapour permeable according to DIN/EN ISO 7783-2 class 1. Washable according to DIN/EN ISO 11998 und DIN EN 13300, class 3.

Full declaration:

Water, chalk, titanium dioxide, vegetable emulsifier, polyaspartic acid, starch ester polymer, talcum, kaolin, methyl cellulose, isothiazolinone. The product contains max 1g/l VOC. EU limit value for this product (cat. a): 30 g/l (2010).

Application:

The surface must be absorbent, dry, solid, clean and free of dust and grease and be free of parting agents, cracks, scum and fungi. Stir well before use! Apply by brush or roller at room temperatures above 12 °C.

Drying time:

At 20°C and 50% relative humidity: first coat after 16 hours, further coatings after 24 hours. Allow to dry for 2 days before applying glaze products.

Container sizes and coverage:

Approx. 150 ml/m² per coat, depending on the absorbency of the surface.

Sizes	Coverage...*
10l	66 m ²

* Coverage per coat

Storage:

Under cool and dry conditions. Shelf life of unopened container 1 years. Close lid tightly when not in use. Protect against frost!

Disposal:

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 20

Cleaning:

Clean equipments immediately after use with warm water and LEINOS Vegetable Soap 930.

Hazard statements:

Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.

Precautionary statements:

Keep out of reach of children.

Do NOT induce vomiting.

Dispose of contents/container according to local regulations.

Hotline for allergy sufferers: ++49 (0) 4163 - 86 74 70

based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: December 10, 2025

LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0 • www.LEINOS.de • info@LEINOS.de