



# Woodworm Free 130

Wood solidifying agent, water-based, protects the wood against mould and insect infestation by physical-mechanical reactions.

Also suitable for porous wood.

**Application range:**

Preventive breathable wood solidifier, protects the wood against mould and insect infestation by physical-mechanical reactions, also for wood work within roofed exterior areas and woodwork used in damp and humid rooms.

**Technical qualities:**

Preventive against mould and insect infestation, water vapour permeable. Also suitable for the restoration (solidification) of old wood. Very effective in disguising wood-work against woodworm and insects etc.

**Colour:**

Colourless, slightly yellow.

**Full declaration:**

Water, aluminium oxide, silicic acid, potassium palmitate, magnesium oxide, potassium chloride, fatty acids. This product contains max. 1 g/l VOC. EU limit value for this product (cat. a): 30 g/l (2010)

**Application:**

Applied by brush or spraying: approx. 100 ml/m<sup>2</sup> per coat. At least two coats necessary! Applied by dipping: Approx. 15 litre/m<sup>3</sup>. The ambient and surface temperature must be higher than +15°C.

**Drying time:**

At 20°C and 50% relative humidity: Subsequent treatment after approx. 24 hours, when the wood is completely dried.

**Container sizes and coverage:**

Application by brush or spray: approx. 100 ml/m<sup>2</sup> per coat. At least two coats are necessary! Dipping respectively steeping: approx. 15 l/m<sup>3</sup>.

Sizes	Coverage...*
1l	10 m <sup>2</sup>
2,5l	25 m <sup>2</sup>
10l	100 m <sup>2</sup>
20l	200 m <sup>2</sup>

\* Coverage per coat

**Storage:**

Under cool and dry conditions, prevent from freezing. Shelf life of unopened containers nearly 5 years.

**Disposal:**

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 20.

**Precautionary statements:**

Safety data sheet available on request.



Keep out of reach of children.  
Avoid release to the environment.  
Dispose of contents/container according to local regulations.

---

To achieve optimum results, please refer to the Technical Data Sheets of all products used. The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.

Status: December 28, 2025

---

**LEINOS • Reincke Naturfarben GmbH • Industriestraße 3 • 21640 Horneburg, Germany**  
**Tel. +49 (0) 41 63 - 86 74 7-0 • [www.LEINOS.de](http://www.LEINOS.de) • [info@LEINOS.de](mailto:info@LEINOS.de)**